

Technical Specifications

Model t278d	DK399A
Processor & Speed	2.6HT GHz/800 Intel® Pentium® 4 Processor – PGA478
Chipset	Intel® 865G
Motherboard	P4SD-LA-GL6E
RAM	256/2700 MB DDR SDRAM
Maximum	4 GB (4x1024MB DDR SDRAM)
Sockets	Four 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	Three
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	8KB Data Cache + Trace Cache L1, 1 MB L2 Integrated on Processor module
Hard Drive	80 GB (7200 RPM)
Optical Drive	DVD+R/RW Drive
Transfer rates	Write: Up to 10x (CD-RW) Write: Up to 16x (CD-R) Write: Up to 4x (DVD+RW) Read: Up to 40x (CD-RW) Read: Up to 40x (CD-R/CD-ROM) Read: Up to 8x (DVD+RW)
Diskette Drive	None
6 in 1 Card Reader	Compact Flash I/II; Memory Stick; MMC/SD; Smart Media
Fax/Data Modem	V.92 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V.42
EIA Fax Commands	Class 1
Video Graphics	AGP 8X Graphics Card
Controller	nVidia GeForce4™ MX-440
Video Memory	64 MB DDR, not upgradeable
Video Connectors	Composite & S-Video – PAL or NTSC
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
MPEG-1/2	MPEG-2 for full-screen, full-motion digital video
TV Tuner	TV Tuner Card
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Jaguar, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	6= USB, 1= serial, 1= parallel, 2=1394
Front I/O Connector	2= USB, 1= 1394; 6 in 1 Card Reader; 1= Microphone; 1= Line In; 1= Headphone
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	1= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse